

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



PCT

(43) International Publication Date
10 February 2005 (10.02.2005)

(10) International Publication Number
WO 2005/013430 A1

(51) International Patent Classification⁷: H01R 13/193,
4/48, 12/04

SC, SD, SE, SI, SK, SL, SY, SZ, TJ, TM, TN, TR, TT, TZ,
UA, UG, UZ, VC, YU, ZA, ZM, ZW only: FCI [FR/FR];
145/147, rue Yves Le Coz (FR).

(21) International Application Number:

PCT/SG2004/000231

(72) Inventor; and

(22) International Filing Date: 30 July 2004 (30.07.2004)

(75) Inventor/Applicant (for US only): SOH, Lip Teck
[MY/MY]; 22 Jalan Timah Tujuh, Taman Sri Putri (MY).

(25) Filing Language:

English

(74) Agent: ELLA CHEONG SPRUSONG & FERGUSON
(SINGAPORE) PTE LTD; P.O. Box 1531, Robinson
Road Post Office, Singapore 903031 (SG).

(26) Publication Language:

English

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AB, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, GR, HR, HU, IE, IL, IS, IT, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SB, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.


(30) Priority Data:
200304106-8 1 August 2003 (01.08.2003) SG

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: CONNECTOR

500



WO 2005/013430 A1

(57) Abstract: A connector (10) for electrically connecting two electrical points (44, 45), the connector having one or more connector terminals arranged in a connector housing (20), the connector terminal comprises a resilient arm portion (32) which bends or deflects about a first pivot portion (34) when the connector terminal is compressed initially and resilient arm portion bends or deflects about a second pivot point (35) when the connector terminal is further compressed subsequently.

BEST AVAILABLE COPY